

CM-YC3500

DIESEL GENERATOR SET / OPEN + SILENT



OPEN SET



SILENT SET

3,500 kVA

STANDBY POWER

3,125 kVA

PRIME POWER

50 Hz

FREQUENCY

400/230 V

VOLTAGE

Yuchai YCC105TA4200-G30

3 phase · 0.8 PF · 1500 rpm

Configuration	Typical application
Open (skid-mounted)	Plant rooms, container frames, OEM builds
Silent (acoustic canopy)	Approx. 75 dB(A) at 7 m, weatherproof
Containerised	ISO footprint, walk-in or standard, up to 45 ft

Enclosure dimensions, weights and tank size are issued with the quotation.

GENERAL CHARACTERISTICS

CM-YC3500 · 50 Hz · 3 Phase

RATED PERFORMANCE

Standby Power (kVA)	3,500
Standby Power (kW)	2,800
Prime Power (kVA)	3,125
Prime Power (kW)	2,500
Power Factor (Cos Phi)	0.8
Diesel Engine	YCC105TA4200-G30
Frequency (Hz)	50
Rated Speed (rpm)	1500
Phase	3
Standard Voltage (V)	400/230

POWER DEFINITIONS

STANDBY POWER (ESP)

Available for supplying emergency power during a utility interruption. The stated rating follows ISO 8528-1; overload is not permitted.

PRIME POWER (PRP)

Available for an unlimited number of annual operating hours in variable-load applications, in accordance with ISO 8528-1.

TERMS OF USE

Nominal power is stated at 25 °C inlet-air temperature, 100 kPa barometric pressure (100 m A.S.L.) and 30% relative humidity.

RATED OUTPUT CURRENT BY VOLTAGE

Rated voltage	Standby current (3,500 kVA)	Prime current (3,125 kVA)
400/230 V	5051.8 A	4510.5 A
380/220 V	5317.7 A	4747.9 A
415/240 V	4869.2 A	4347.5 A